




General	Unit	TopGrinder with Vacuumsystem
Authentication		CE-approved equipped with double manual operation
Weight	kg	445 kg
Dimensions L x W x H	mm	1435 x 1100 x 1510 mm
Work height	mm	950 mm
Worksheet	mm	1280 x 780 mm
Minimum workpiece dimension	mm	20 x 20 mm
Maximum workpiece height	mm	120 mm
Maximum workpiece width	mm	780 mm / length unlimited
Maximum load work table	kg	100 kg
Operation		Double manual operation
Optional Wet Extraction System		WES3000 Control by deburring machine or on extractor
Connection Wet Extraction System	mm	Ø 120 mm
Prescribed Extraction capacity	m ³ /h	1500 m ³ /h
Prescribed Extraction speed	m/s	19 m/s
Aggregates		
Number of adjustment stations		1
Number of heads		2 (2x M12)
Brush version	mm	Standard abrasive brush: Ø 255 mm. Various variations of brushes possible
Brush power	kW	0,75 kW motors with frequency regulation
Rotation speed	r.p.m.	150 - 1500 r.p.m.
Adapter		M12/M14 voor diverse slijpgereedschappen
Worktable		
Mat version		Rubber; special friction version
Fixation		Vacuum System in worktable (standard)
Mat product	kW	2,2 kW
Optional magnets	DaN	2 or 4 magnets 300, DaN (*) per piece In addition to vacuum system For ferrous product fixation
Electrical specifications		
Input voltage	V	400 V (3L+N+PE)
Frequency	Hz	50 Hz
Input current	A	10 A
Power	kW	6 kW
Power plug	CEE	400 V CEE plug / 16 A / 5 pins

(*) For optimum theoretical holding power, respect setting conditions 100%.