## F1200



## **TECHNICAL SPECIFICATIONS**

General	Unit	F1200 with Vacuum or Magnet support
Authentication	CE WIN EN 1000	CE-approved with dual emergency stop circuit and reset system
Weight	kg	2,650 kg
Dimensions L x W x H	mm	2037 x 2178 x 2090 mm
Work height	mm	900 mm
Minimum workpiece size	mm	80 x 80 mm Vacuum or 50 x 50 mm Magnet
Minimum workpiece height	mm	0.6 mm (L and W $\geq$ 5 x H)
Maximum workpiece height	mm	170 mm
Maximum workpiece widht	mm	1200 mm
Conveyor belt speed	m/min	Frequency controlled 0.3 - 5 m <sup>1</sup> /min
Operation panel		HMI Touchscreen
Optional Wet Extraction System		WES6000 Control by deburring machine or extractor
Connection Wet Extraction System	mm	Ø 300 mm
Prescribed Extraction Capacity	m³/h	4000 m³/h
Prescribed Extraction Speed	m/s	19 m/s
Aggregates		
Number of stations		3 aggregates: abrasive belt / 1x 2 brushes / 1 x 2 brushes
Abrasive belt	mm	Grinding belt 1230 mm wide  Quick change system
Brushes	mm	4 pieces, Ø 255 mm Universal clamping system
Transportation		
Conveyor belt version	°C	VAC or MAG EPDM friction rubber, heat resistant up to 140 °C
Conveyor belt set-up	kW	Equipped with Vacuum system (2.2 kW) or Magnet fixation Choose Vacuum for non-ferro; Magnet for ferro metals
Maximum transport conveyor load	kg	300 kg
Cleaning conveyor belt		Cleaning brush with dust collector
Setting workpiece height		Transport table electric adjustable with digital reading
Components		
Grinding unit		Frequency controlled grinding head with sanding drum
diffiding diffe	mm	
	mm kW	Grinding belt size: 1230 x 1900 mm Motor power 7.5 kW
Brush version	mm	Abrasive brush: Ø 255 mm
DI USIT VELSIOIT	111111	Oscillating system, cross action
		Equipped with automatic workpiece height compensation
		Various types of brushes available, grit K40 - K320
Brush power	kW	2.2 kW motors with frequency control
Press rollers	100	Heavy duty press rollers; rubber with a oil and heat resistant coating
Electrical specifications		reary saty press toners, robber with a on and neartesistant coating
•	V	100 V
Input Voltage	V	400 V
Frequency	Hz	50 Hz
Input Current	A	32 A
Connected Load	kW	16 kW
400V plug	А	32 A