


WES6000

TECHNICAL SPECIFICATIONS



Q-FIN

Quality Finishing Machines

| General | Unit | WES6000 |
|---------------------------------|-----------------------------------------------------------------------------------|-------------------------------------------------------------|
| Authentication |  | CE-approved |
| Weight without water | kg | 495 kg |
| Water content | l | 550 l |
| Water use | l/h | 7 l/h |
| Dimensions L x B x H | mm | 2070 x 1090 x 2560 mm |
| Fan | kW | 7.5 kW |
| Maximum capacity | m ³ /h | 6000 m ³ /h |
| Extraction speed | m/s | 19 m/s |
| Noise | dBA | 72 dBA |
| Control of exhaust installation | | Control by power switch or external machine |
| Standard | | |
| | | LED indicator: blue for in operation, red for filling |
| | | Electronic floating system, automatic filling and levelling |
| | | Fully manufactured in stainless steel |
| | | 5 collectors (for easy cleaning) |
| | | Exhaust with silencer |
| | | Spillway front 2" |
| Operation | | |
| Motor | | Ventilator 7.5 kW |
| Filter | | Labyrinth + deflection grid |
| Consumption | | Tap water |
| Water inlet connection | inch | ¾" or ½" GARDENA-Fitting |
| Air inlet connection | mm | Ø 300 mm |
| Electrical specifications | | |
| Input Voltage | V | 400 V (3L+N+PE) |
| Frequency | Hz | 50 Hz |
| Input Current | A | 25 A |
| Connected load | kW | 12 kW |
| 400V plug | A | 400 V CEE plug / 32 A / 5 pins |